



PRODUCT BULLETIN: PURPLE PRIMER

PRODUCT HIGHLIGHTS: (PRODUCT CODE - APP)

- Purple-tinted aggressive primer for use on PVC and CPVC pipe and fittings.
- Lo-V.O.C. Solvent Cement meets California South Coast Air Quality Management District (SCAQMD) 1168/316A or BAAQMD Method 40 and various environmental requirements.
- Maximum VOC per SCAQMD 1168/316A or BAAQMD Method 40: 550g/L

GENERAL DESCRIPTION:

Atoot Purple primer removes Surface dirt, grease and grime as well as softens the pipe surface to allow a fast, secure solvent weld. It is for use in areas where plumbing code calls for verification that a primer has been used.

PHYSICAL/CHEMICAL PROPERTIES:

Appearance : Purple Liquid
Relative Density : 0.84
Shelf Life: 2 years from MFG Date

APPLICATION :

For all CPVC, UPVC & PVC pipe.

STANDARD TECHNICAL INFORMATION ON PURPLE PRIMER:

Note: The above mentioned performance of Primer are under lab conditions. There may be variance under field conditions based on weather, temperature, individual handling & pipe characteristics.

AVAILABILITY:

PRODUCT NUMBER	SIZE	(Inner carton) PACK	(Master carton) PACK	CARTON WEIGHT (KG)
APP08	8 oz./237 ml	24	48	12.00
APP16	16 oz./473 ml	24	24	15.20
APP32	32 oz./ 946 ml	12	12	12.50

PRODUCT NUMBER	SIZE	(Inner carton) PACK	(Master carton) PACK	CARTON WEIGHT (KG)
APP250	250ml	24	48	12.00
APP500	500 ml	24	24	15.20
APP1LT	1000ml	12	12	12.50

APPLICATION:

Read all directions carefully before using this product. Do not breathe vapors. Use only in well ventilated areas. If forced air ventilation is used, be sure it does not cause a fire hazard from solvent vapors. If adequate ventilation cannot be provided, wear a NIOSH-approved respirator for organic solvents. Do not use or store near heat, sparks, or flames. Do not smoke, eat or drink when using. Do not take internally. Vapors may accumulate in low places and may ignite explosively. Store and use at temperature between 0°F to 110°F. At temperatures outside of this range, special care must be taken to prepare good joints and prevent exposures to solvents. Stir or shake before using; if jelly-like, don't use. Keep container closed when not in use. Avoid eye and skin contact-wear safety glasses with side shields and wear rubber gloves.

1. Square pipe ends and remove all burrs and dirt.
2. Check dry fit of pipe and fitting. Pipe should easily go 1/3 of the way into the fitting. If the pipe bottoms, it should be snug.
3. Use a suitable applicator at least 1/2 the size of the pipe diameter. For larger size pipe systems use a natural bristle brush or roller.
4. Apply thoroughly to inside of the fitting socket and to the outside surface of the pipe to the depth of the fitting. Apply a second coat of primer to fitting socket.
5. While primer is still wet use an appropriate solvent cement for the pipe being joined. Follow application instructions from cement can.

Do not test with Air. This product is not for caustic or acidic chemical solutions. Consult Bharat Pipe Industries Technical department for more information.

SHELF LIFE:

2 years in tightly sealed containers from the date code of manufacture as stamped on the bottom of the container. Stability of the product is limited by the evaporation of the primer when the container is opened. Evaporation of primer will cause the cement to thicken and reduce its effectiveness. To be stored in cool, dry environment below 35°C.

QUALITY ASSURANCE:

Purple Primer by Bharat Pipe Industries is carefully evaluated to assure that consistent high quality is maintained. A batch identification code is stamped on each can and assures traceability of all materials and processes used in manufacturing this Purple Primer.

PRECAUTIONS:

- Fire** Use dry chemical, foam, or carbon dioxide extinguisher. Water spray may be applied to reduce potential vapors or for cooling. Burning liquid extinguished with water will float and may re-ignite on surface of water.
- Spill** Remove all sources of ignition and ventilate area. Personnel cleaning up spill should wear appropriate personal protective equipment, including respirators if vapor concentrations are high. Soak up spill with absorbent material. Put absorbent material in covered, labeled metal containers. Dispose of in accordance with local regulations.

DO NOT REUSE EMPTY CONTAINER. KEEP OUT OF REACH OF CHILDREN.

**FIRST AID:**

Ingestion: If swallowed, **Do not induce vomiting**. Drink Water and call a doctor or poison control immediately.
FIRST AID INSTRUCTIONS CALL +91 7045430101

Inhalation: If overcome with vapors, remove to fresh air. If not breathing, give artificial respiration.
If breathing is difficult, give oxygen. Call a physician.

Eye Contact: Flush with plenty of water for 15 minutes and call a physician.

Skin Contact: Wash skin with plenty of water and soap for at least 15 minutes.
If irritation develops, get medical attention.

SPECIAL PRECAUTION:

Do not use a dry granular calcium hypochlorite as a disinfecting material for water purification in potable water piping systems. The introduction of granules or pellets of calcium hypochlorite with PVC and CPVC solvent cement and primers (including their vapors) may result in a violent chemical reaction if a water solution is not used. It is advisable to purify line by pumping water into the piping system- this solution will be nonvolatile. Furthermore, dry granules calcium hypochlorite should not be stored or used near solvent cements and primers.

IMPORTANT NOTE:

This product is intended for use by skilled individual at their own risk. These suggestions and data are based on information we believe to be reliable. Installer should verify for themselves that they can make satisfactory joints under varying conditions. Towards this end, it is highly desirable that they receive personal instruction from trained instructors or experienced installers. Contact Bharat Pipe Industries for additional information or instructions.

WARRANTY:

Bharat Pipe Industries warrants that all new **Atoot** products shall be good quality and free from defects in material and workmanship for shelf life as indicated on the product. If any **Atoot** product becomes defective, or fails to conform to our written limited warranty under normal use and storage conditions, Then Bharat Pipe Industries will without charge, replace the non conforming product. However, this limited warranty shall not extend to, nor shall Bharat Pipe Industries will be responsible for, damage or loss resulting from accident, misuse, negligent use, improper application, or incorporation of **Atoot** product in to other products. In addition, any repackaging of **ATOOT** products also shall void the limited warranty. Bharat Pipe Industries shall not be responsible for, nor does this limited warranty extend to, consequential damage or incidental damage or expense, including without limitation, injury to persons or property or loss of use. Please refer to our standard BHARAT PIPE INDUSTRIES warranty for additional provisions.

**IPS is a trademark of IPS Corp , USA*

**Oatey is a trademark of Oatey*